


V3070-GPT/GAB (HSV10)

Graphic Symbol

繪圖符號



Ordering Code

型號說明 V3070 1 GPT 2 @ 3 # 4 * 5 D24 6 DG 7 25 8

1

Cartridge solenoid check valve
插入式電磁止回閥

V3070(10W-2) 二口二位 Poppet 2-way


2

Manifold type
油路塊總類選項

GAB: A ↔ B
GPT: P ↔ T

3

Operation
油路方向功能選項



4

Option: with filter
附濾網裝置選項

S: With Filter 有濾網
N: Without Filter 無濾網

5

Option: with manual
附手動輔助裝置選項

P: Push-style Manual Override
P: 推 (向外推移式)
M: Screw-out Konb Style
M: 旋鈕式(開) 逆時鐘方向 ↺
T: Push and Twist Style
T: 推桿附扭轉

N: Option
N: 標準(輔助裝置不可調)
Screw-in Konb Style
旋鈕式(關) 順時鐘方向 ↻
Manual Override
固定輔助裝置

6

Coil type
線圈型式

D12: DC12V A22: AC220V
D24: DC24V A38: AC380V
A24: AC24V RA1: RAC220V
A11: AC110V RA2: RAC220V

7

Terminations
接線方式

DG: DIN43650 插頭式
DL: Lead wires(2) 出線2條式

8

Max pressure
最高壓力

25: 250bar(3500psi)

Millimeters/(inch)